Mono 40

	Mono 40 holder set for wooden panels	Front arm, straight Ø 12 mm	Bracket Ø 12 mm for hanging rail Ø 15 mm
	พริสา์ตพ	<u>.</u>	2
Dimensions	☑ 40 mm	150 300 9 12	250
Characteristics	Max. weight load = 20 kg per holder Observe the assembly and operating instruction	Max. weight load = 10 kg	Coat-hangers can slide along the entire length of the hanging rail. Max. weight load = 10 kg per bracket
Order number	silk 915-984.30	silk 150 mm	silk
	Incl. fixing set and silver cover cap.		At least 2 brackets are required per hanging rail.

vísplay | Manual 01.13

Mono 40



Hanging rail Ø 15 mm	Bracket Ø 12 mm for wooden shelf	Clamping bracket for glass shelf	Scliss
1	<u> </u>		
ø 15	300	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	100 x
lto			R 20.5
To be inserted into brackets for hanging rail.	Max. weight load = 10 kg per bracket Max. display depth = 320 mm Drawing no. 286-612 Wooden shelf	Max. weight load = 10 kg per bracket Max. display depth = 320 mm Drawing no. 286-613 Glass shelf 8 mm	Prevents scratches on hanging rails and front arms in silk or stainless steel. To clip into coat hanger hook (Ø 3.4–3.8 mm).
silk Ito 520–2445 mm ⊙ 906-329.30	silk	silk ■ 340-988.30	<u>transparent</u> ● 929-449.0 2
520–795 mm => 2 brackets 796–1195 mm => 3 brackets 1196–1595 mm => 4 brackets 1596–2445 mm => 5 brackets	At least 2 brackets are required per shelf.	At least 2 brackets are required per shelf.	Set of 100 pcs.

46vísplayManual 01.13