























| | <p>Frame Fixing axis 617.5 mm</p>  | <p>Frame Fixing axis 1242.5 mm</p>  | <p>Wall fixing bracket set for frame</p>  | | | | | | | | | | | | |
|-------------------------------|--|--|--|-------------------|-----------|---|-------------------|---|--|---|-------------------|---|--|---|-------------------|
| <p>Dimensions</p> |  |  |  | | | | | | | | | | | | |
| <p>Characteristics</p> | <p>For attachment to the wall.</p> <p>Max. weight load: - Frame 632.5 x 632.5 mm = 80 kg - Frame 1282.5 x 632.5 mm = 160 kg</p> <p>📄 Drawing no. 312-463 Back panel 600 x 600 mm 312-464 Back panel 600 x 1250 mm</p> <p>⚠️ Observe the assembly and operating instruction</p> | <p>For attachment to the wall.</p> <p>Max. weight load = 160 kg</p> <p>📄 Drawing no. 312-465 Back panel 1225 x 1250 mm</p> <p>⚠️ Observe the assembly and operating instruction</p> | <p>The fixtures and wall must be able to support a traction of min. 1 kN (100 kg) per point of fixture. The type of fixtures for the wall screw fittings must be determined by the assembly fitter according to the wall structure.</p> <p>⚠️ Observe the assembly and operating instruction</p> | | | | | | | | | | | | |
| <p>Order number</p> | <p>cto</p> <table border="1"> <tr> <td>632.5 mm</td> <td>⊙</td> <td>322-331.07</td> </tr> <tr> <td>1282.5 mm</td> <td>⊙</td> <td>322-332.07</td> </tr> </table> | 632.5 mm | ⊙ | 322-331.07 | 1282.5 mm | ⊙ | 322-332.07 | <p>cto</p> <table border="1"> <tr> <td></td> <td>⊙</td> <td>322-333.07</td> </tr> </table> | | ⊙ | 322-333.07 | <p>traffic white</p> <table border="1"> <tr> <td></td> <td>⊙</td> <td>332-183.23</td> </tr> </table> <p>2 wall fixing bracket sets are required per frame.</p> | | ⊙ | 332-183.23 |
| 632.5 mm | ⊙ | 322-331.07 | | | | | | | | | | | | | |
| 1282.5 mm | ⊙ | 322-332.07 | | | | | | | | | | | | | |
| | ⊙ | 322-333.07 | | | | | | | | | | | | | |
| | ⊙ | 332-183.23 | | | | | | | | | | | | | |




| | | | |
|---|---|---|--|
| <p>Back panel holder for frame</p>   <p>ⓘ <i>Observe the assembly and operating instruction</i></p> <hr/> <p>black steel duro ● 066-861.26</p> | <p>Wall frame Fixing axis 617.5 mm</p>   <p>Standing on the floor fixed to the wall. Max. weight load = 240 kg</p> <p>📄 Drawing no. 312-466 Back panel 600 x 2382 mm</p> <p>ⓘ <i>Observe the assembly and operating instruction</i></p> <hr/> <p>cto ○ 322-334.07</p> <p>Glides (2 pcs.) must be ordered separately.</p> | <p>Glide Ø 50 mm</p>   <p>Adjustable height 62–90 mm. Max. weight load = 60 kg per glide</p> <hr/> <p>black steel duro ○ 332-185.26</p> | <p>Glide Ø 50 mm with pin</p>   <p>Adjustable height 62–90 mm. Max. weight load = 60 kg per glide</p> <hr/> <p>black steel duro ○ 332-186.26</p> |
|---|---|---|--|

| <p>Wall fixing bracket for wall frame</p> | <p>Back bar 35 x 20 mm</p> | <p>Front arm, straight 30 x 15 mm</p> | <p>Front arm, stepped 30 x 15 mm</p> |
|---|---|--|---|
|  |  |  |  |
|  |  |  |  |
| <p>Max. weight load = 200 kg</p> <p>ⓘ <i>Observe the assembly and operating instruction</i></p> | <p>Max. weight load = 40 kg</p> | <p>For hanging on back bar. Max. weight load = 20 kg</p> | <p>For hanging on back bar. Max. weight load = 20 kg</p> |
| <p>traffic white</p> <p>○ 332-188.23</p> <p>Incl. fixing set.</p> | <p>chrome</p> <p>○ 371-603.01</p> <p>silk</p> <p>○ 371-603.30</p> | <p>chrome</p> <p>○ 371-664.01</p> <p>silk</p> <p>○ 371-664.30</p> | <p>chrome</p> <p>○ 371-666.01</p> <p>silk</p> <p>● 371-666.30</p> |




Side hanging frame 30 x 15 mm



Max. weight load = 40 kg

| | | |
|-----------|----------------------------------|-------------------|
| chrome | | |
| 617.5 mm | <input type="radio"/> | 371-601.01 |
| 1242.5 mm | <input checked="" type="radio"/> | 371-604.01 |
| silk | | |
| 617.5 mm | <input type="radio"/> | 371-601.30 |
| 1242.5 mm | <input type="radio"/> | 371-604.30 |

Bracket for wooden shelf



Max. weight load = 40 kg

Max. display depth = 386 mm


📄 Drawing no.
271-711 Wooden shelf 19 mm

| | | |
|---------------|-----------------------|-------------------|
| cto | | |
| | <input type="radio"/> | 945-590.07 |
| Set of 2 pcs. | | |

Sliss



100 x



Prevents scratches on hanging rails and front arms in silk or stainless steel.

To clip into coat hanger hook (Ø 3.4–3.8 mm).

| | | |
|-----------------|----------------------------------|-------------------|
| transparent | | |
| | <input checked="" type="radio"/> | 929-449.02 |
| Set of 100 pcs. | | |