


















	Xero Struc 8 upright	Connector bar for fixing axis 617.5 mm	Glide Ø 72 mm
Dimensions	 	 	 
Characteristics	<p>Slot width for 2 brackets.</p> <p>Max. weight load = 100 kg per 1000 mm</p> <p>Merchandise supports for a display at fixed intervals with back bars, front arms and hooks, hanging frames or shelves, see Stabilo range.</p> <p>🔧 <i>Observe the assembly and operating instruction</i></p>	<p>For the use of axis-independent accessories from the Stabilo range.</p>	<p>Adjustable height 83–120 mm.</p> <p>🔧 <i>Observe the assembly and operating instruction</i></p>
Order number	<p>natural anodised aluminium</p> <p>2315 mm ☉ 934-122.05</p> <p>1000–4000 mm ☉ 934-121.05</p> <p>End cap and glide must be ordered separately if required.</p>	<p>natural anodised aluminium</p> <p>● 300-947.05</p>	<p>silver mat</p> <p>☉ 300-581.48</p> <p>Incl. fixing set.</p>



<p>Glide Ø 72 mm with pin</p>    <p>Adjustable height 83–120 mm.</p> <p>ⓘ <i>Observe the assembly and operating instruction</i></p> <hr/> <p>silver mat ○ 300-822.48</p> <p>Incl. fixing set.</p>	<p>Ceiling fixing device</p>    <p>Adjustable height 75–105 mm.</p> <p>ⓘ <i>Observe the assembly and operating instruction</i></p> <hr/> <p>silver mat ○ 300-810.48</p> <p>Incl. fixing set.</p>	<p>Wall fixing bracket</p>    <p>Adjustable distance to wall 45–68 mm.</p> <p>The fixtures and wall must be able to support a traction of min. 1.6 kN (160 kg) per point of fixture. The type of fixtures for the wall screw fittings must be determined by the assembly fitter according to the wall structure.</p> <p>ⓘ <i>Observe the assembly and operating instruction</i></p> <hr/> <p>silver mat ● 300-563.48</p>	<p>End cap</p>   <hr/> <p>silver ● 981-566.05</p>
---	--	---	---